



Project Name _____

FOG Enforcer 1150 FE1150

LARGE CAPACITY HDPE GREASE INTERCEPTOR

Specification: FOG ENFORCER FE1150, 100 GPM grease interceptor with 1,150 lb. grease design capacity. Interceptor has a limited lifetime warranty and is made in the USA out of seamless, rotationally molded High Density Polyethylene with 3/8" uniform wall thickness. Interceptor designed for above or below ground installation. Interceptor includes a dual adjustable lid system, external, vented flow control fitting, sample port access, and multiple outlet options. Steel encased composite gasketed cover and collar. Standard 18" diameter corrugated drainage pipe provides a water / gas tight seal and have a minimum of 20,000 lbs. load capacity. The lid is designed in accordance with the loading requirements of AASHTO H20.

Function: Used in restaurants, kitchens, institutions, industrial facilities such as food processing and packaging plants and other types of food processing areas where fat, oil and grease (FOG) drains with the wastewater. Narrow width permits access through doorways and down stairwells. High Density Polyethylene construction ensures a lightweight installation process (two people can move and install it).



**Note: The FE 1150 does not meet PDI standard if outfitted with an internal flow control (-OP suffix). The PDI standard is only valid for the external flow control fitting.*

MODEL NO.	GPM (Flow Rate)	GREASE DESIGN CAPACITY (Lbs.)	LIQUID CAPACITY (GAL)	SHIPPING WEIGHT (Lbs.)
FE 1150	100	1,150	300	275

- SUFFIX** **OPTIONAL VARIATIONS**
- AK High water anchor kit (set of two)
 - C Lid extension (specify "C" dimension required)
 - CL Hold down brackets for lid (when installed above ground)
 - DI Ductile iron lid and collar
 - DP Dosing pump
 - EP Enzyme port
 - FL-C Membrane clamp kit
 - HLA High level alarm
 - LHSI 4" no hub inlet on left hand side
 - LHSO 4" no hub outlet on left hand side
 - OP Internal flow control*
 - RHSI 4" no hub inlet on right hand side
 - RHSO 4" no hub outlet on right hand side
 - SB Sediment bucket
 - SP External Sampling Port
 - T Female threaded connections



Job Name: _____ Page No: _____
 Section No: _____ Contract: _____
 Schedule No: _____ Purchase Order No: _____